imageCLASS LBP841(dn & LBP843(x





VERSATILE BUSINESS PRINTING CANVAS FOR YOUR CREATIVITY







Business Can be simple



* Operation Panel for LBP843Cx.

MADE FOR BIGGER POSSIBILITIES

Canon's imageCLASS LBP841Cdn and LBP843Cx are designed to scale productivity in the office. Look forward to uncompromised performance and quality as well as integrated capabilities for easy management. With versatile duplex printing and power saving features, you will enjoy savings by using lesser paper and reducing energy consumption.

EVERYDAY EASE OF USE



AMAZING PRINT SPEED

Enjoy continuous work productivity with quick first prints and print speeds of 26ppm(A4) for LBP841Cdn and 31ppm(A4) for LBP843Cx.



ABSOLUTE COMPATIBILITY

Both imageCLASS LBP841Cdn and LBP843Cx are equipped with industry standard PCL 6 print language, especially useful for enterprises managing a fleet of print devices. Expect seamless compatibility and integration with your IT systems.

MANAGEMENT MADE SIMPLE

Keep track of system status and device settings from your desk and away from the printer. With the Remote UI, you can access and manage your printer conveniently from the web browser on your computer, smartphone or tablet and mobile device.

Canon			ne: LBP843Cx ime (Serial No.): LBP843Cx		
🚷 Remote UI: Portal				Language: English	Mail to System Manager
					Last Updated: 23/05 2016 18:48:38
Device Basic Informa	tion				
Device Status					
The printer is read;	r.				
Error Information					
There is no error.	ation				
Paper Information					
Paper Source	Remaining Paper	Paper Size	Paper Type		
Multi-Purpose Tray	None	A4	Plain		
Drawer 1	ок	A4	Plain		
Toner Cartridge Inf	ormation				
Color Remainin	ig Toner				
Cyan	100%				
Magenta	100%				



VERSATILE PAPER HANDLING

Supporting a diverse range of print media sizes from A5 to A3, the LBP841Cdn and LBP843Cx can handle high-volume tasks with paper cassette options, up to a maximum input capacity of 2,000 sheets.



HASSLE-FREE MAINTENANCE

Canon's All-in-One toner cartridge delivers unrivalled print quality with minimal effort. To further save and reduce frequency of replacement, it also offers high-yield toner cartridges (Black: 13,000 pages and C/M/Y: 16,500 pages) for a lower cost-per-print.



*For illustration purposes only.

SMOOTH CONNECTIVITY

SEAMLESS NETWORK

Both the LBP841Cdn and LBP843Cx feature gigabit network connectivity, allowing speedy data transfers of up to 1000Mbits/ second. This means easier, faster and seamless print jobs, giving you more time to focus on work that truly matters.

Explore boundless possibilities that let you print documents from your mobile devices via Canon's PRINT Business app*.

*Printer must be connected to the same wireless network as the mobile device.



ECO-FRIENDLY CAPABILITIES



DUPLEX SAVINGS

Save on paper usage with double-sided prints. Not only fulfilling the office needs for highvolume printing tasks, 2-sided printing is now also automated and effortless. Ideal for costefficiency in every work space.



GREEN SUSTAINABILITY

Reduce power consumption with Sleep Mode that uses as little as 3W. Go further with Auto Shutdown by configuring the printer to shut down when a specified time has elapsed after entering Sleep Mode, saving your expenses and the environment.

EXPECT MORE WITH LBP843Cx



ENHANCED CAPABILITIES

Enjoy greater benefits on the LBP843Cx with features such as native Secure Print* and Department ID, ensuring print confidentiality and costs tracking. By integrating with any existing uniFLOW managed print environment, you can also customise the workflow based on your exact requirements. Print efficiency has never been better.

*Requires SD Card-C1 option



EASY DIRECT PRINTING

This feature allows you to print PDF, TIFF or JPEG files directly from your USB device memory on the LBP843Cx. No installing of printer drivers needed.



imageCLASS LBPA41Cdn & LBPA43C>

SPECIFICATIONS

ГВЬӨАТС	d n & L B P B 4 3 C	X LBP841Cdn	LBP843Cx			
PRINT						
Printing Method		Colour Laser Beam Printing				
	A4	26 / 26ppm (mono / colour)	31 / 31ppm (mono / colour)			
Print Speed	A3	15 / 15ppm (mono / colour)	15 / 15ppm (mono / colour)			
Print Resolution		600 × 600dpi, 1,200 × 1,200dpi, 9,600 (equivalent) × 600dpi				
First Print Out Time (FPOT)		Approx.7.9 / 9.9 seconds (mono / colour)				
Print Language		UFR II, PCL6 (45 scalable fonts) UFR II, PDF, XPS, PCL6 (93 scalable fonts)				
Warm-up Time (from power on)		29 seconds or less				
Recovery Time (from sleep mode)		Approx. 9 seconds				
Auto Duplex Printing		Standard				
Available Paper Size for Auto Duplex Print		A3, B4, A4, B5, A5, Legal ¹¹ , Letter, Executive, Foolscap				
PAPER HANDLING						
Paper Input	Standard Cassette	250 sheets				
	Multi-Purpose Tray	100 sheets				
	Maximum Paper Capacity	2,000 sheets				
Paper Output		250 sheets (face down)				
	Standard Cassette	A3, B4, A4, B5, A5, Legal ¹¹ , Letter, Executive, Foolscap				
Paper Size		Custom: width 148.0 to 297.0mm, length 182.0 to 431.8mm				
	Multi-Purpose Tray	A3, B4, A4, B5, A5, Legal ⁻¹ , Letter, Executive, Foolscap, Index Card (3"x 5"), Envelope: ISO-C5, No.10, Monarch, DL Custom: width 76.2 to 304.8mm, length 120.0 to 457.2mm				
Paper Weight	Standard Cassette	60 to 128g/m ²				
ruper weigin	Multi-Purpose Tray	60 to 220g/m ²				
Paper Type		Plain, Heavy, Label, Envelope				
CONNECTIVITY & SOFTWARE						
Standard Interface		USB 2.0 High Speed 10Base-T / 100Base-T				
Network Interface		Supported protocol: TCP / IP (Frame type: Ethernet II), SMB (SMB is only available for LBP843Cx) Print application: LPD, RAW, IPP / IPPS, FTP, WSD				
Mobile Print		Canon PRINT Business, Canon Print Service				
Compatible Operating Systems		Windows® 10 (32 / 64-bit), Windows® 8.1 (32 / 64-bit), Windows® 8 (32 / 64-bit), Windows® 7 (32 / 64-bit), Windows® Vista (32 / 64-bit), Windows® Server 2012 (64-bit), Windows® Server 2008 (32 / 64-bit), Window				
GENERAL SPECIFICA	TIONS					
Device Memory		512MB	1GB			
Operation Panel		5-line LCI	D Display			
Dimensions (WxDxH)		545 x 591 x 361.2mm				
Weight		Approx. 34kg				
	Maximum	1,420W or less				
Power Consumption						
	During Operation	Approx. 530W	Approx. 540W			
	During Standby	Approx. 22.5W				
	During Sleep	Approx. 3W (USB connection), Approx. 1.5W (Wired LAN connection)				
Noise Level*3	During Operation	Sound Power: 6.6B or less, Sound Pressure: 51dB	Sound Power: 6.7B or less, Sound Pressure: 52dB			
	During Standby	Inaudible "4				
Power Requirement		220 to 240V, 50 / 60Hz				
Operating Environment		Temperature: 10 to 30°C Humidity: 20% to 80% RH (no condensation)				
Toner Cartridge ^{*5}	Standard	Cartridge 335E BK: 7,000 pages; Cartridge 335E C/M/Y: 7,400 pages (bundled black: 7,000 pages; bundled C/M/Y: 7,400 pages)				
	High	Cartridge 335 BK: 13,000 pages; Cartridge 335 C/M/Y: 16,500 pages				
Monthly Duty Cycle*		75,000 pages	120,000 pages			
OPTIONAL ACCESSO	DRIES					
Paper Feeder-E1	Paper Capacity	550 sheets				
	Paper Size	A3, B4, A4, B5, A5'7, Legal'1, Letter, Executive, Foolscap Custom: width 148.0 to 297.0mm, length 182.0 to 431.8mm				
	Paper Weight	60 to 128g/m ²				
SD Card-C1		N/A	Yes			
3D Guid-GT		IN/A	162			

¹² Drivers for Mac OS or Linux can be downloaded from www.canon-asia.com when available
¹³ Measured in accordance with ISO 7779, declared noise emission in accordance with ISO 9296
¹⁴ "Inaudible" indicates the sound pressure level of each bystander position is below the ISO 7779 absolute criteria for the background noise level.

Canon

Barcode Printina Kit-F1

Delighting You Always

South & Southeast Asia **Regional Headquarters**

1 Fusionopolis Place, #15-10,Galaxis, Singapore 138522 Tel: 65-6799 8888 Fax: 65-6799 8882

Dealer's Stamp

HONG KONG Canon Hongkong Co. Ltd. Tel: 852-3191 2388 Fax: 852-2369 3800 www.canon.com.hk

INDIA Canon India Pvt Ltd. Tel: 91-124 416 0000 Fax: 91-124 416 0011 www.canon.co.in

CANON OFFICES

MaLAYSIA Canon Marketing (Malaysia) Sdn. Bhd. Tel: 60-3 7844 6000 Fax: 60-3 7845 0505 www.caron.com.my

PHILIPPINES Canon Marketing (Philippines), Inc. Tel: 632-884 9090 Fox: 632-556 1456 www.canon.com.ph

SINGAPORE Canon Singapore Pte. Ltd. Tel: 65-6799 8888 Fax: 65-6799 8882 www.canon.com.sg

N/A

ThallaND Canon Marketing (Thailand) Co. Ltd. Tel: 66-2 344 9990 Fax: 66-2 344 9960 www.canon.co.th

VIETNAM Canon Marketing Vietnam Co. Ltd. Tel: 84-8 3820 0466 Fax: 84-8 3820 0477

⁵ Declared yield in accordance with ISO/IEC 19798.
⁶ Monthly duty cycle value provides a means for comparison of product robustness in relation to other Canon laser devices, and does not refer to actual maximum image output per month
⁷ Optional paper feeder does not support 2-sided printing for A5 size.

CANON BUSINESS PARTNERS

BANGLADESH J.A.N Associates Ltd. Tel: 880-2-966-0601 Fax: 880-2-861-0410 www.jan-bd.com

BRUNEI Interhouse Company Tel: 673-2-653001 Fax: 673-2-653003 www.ihc.com.bn

CAMBODIA i-Qlick Marketing Co., Ltd. Tel: 855-23-996638 Fax: 855-23-996639 www.i-qlick.com

INDONESIA PT. Datascrip Tel : 62-21 2664 8999 Fax : 62-21 6544 811/13 www.datascrip.com

MALDIVES SIMDI Company (Pvt) Ltd. Tel: 960 - 3334421 Fax: 960 - 3334424 www.simdi.com

MYANMAR Myanmar Golden Rock Infernational Co., Ltd. Tel: 95-1 654810 to 19 (10 Lines) Fox: 95-1 654820 Email: sales@mgr.com.mm

Yes

NEPAL International Electronics Concern (P) Ltd. Tel: 977-1 4421991 Fax: 977-1 4421999 www.iec.com.np

WWW.lectors PAKISTAN Shirazi Trading Company (Pvt.) Limited Tel: 92-21-3241 (7659), (7737) or (7746) Fax: 92-21-(3241 7747), (3242 0417) or (3242 0418) www.shirazitrading.com.pk

SRI LANKA Metropolitan Office (Pvt) Ltd. Tel: 94-11 470 0200 Fax: 94-11 470 0267 www.metropolitan.lk

0202W282 © 2016 Canon Singapore Pte. Ltd. All rights reserved.

Uduary 22 (2) 2016 cannon singappie the Lita Air ingins reserved. This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may var by regions. Nothing in this document should be construed as a warrantly. We expressly disclaim any liability or contractual obligations with respect to this document. Canon, imageCLASS, Business Can Be Simple and Canon PRINT Business App are trademarks of Canon inc. and/or its affiliates. Other names may be the trademarks for their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pie. Ltd.