HIGH VOLUME PRINTING AT LOW COST PER PRINT



Print up to **7000 pages** in colour and **6000 pages** in monochrome.



SPILL-RESISTANT INK BOTTLES WITH INTEGRATED SEE-THROUGH TANKS

 Ink bottles are designed with special tips to prevent spillage during ink refilling

• See-through tanks indicate remaining ink levels clearly



Experience crisp, clear black text-suitable for professional presentations, reports and borderless photos up to A4.



Easily connect your smartphone directly to the printer with a single key-press.

| | SPECIFICATIONS | | | G4010 | G3010 | G3000 | G2010 | G1010 | |
|--|---|---|--|---|--|---|----------------------|-----------------------|--|
| PRINT | Maximum Printing Resolution*1 | | | | 4800 x 1200 dpi | | | | |
| | Number of | Number of Ink Bottles | | | 4 (bottles) | | | | |
| | Print | Document: B&W/Colour | ESAT/Simplex | approx. 8.8 ipm/5.0 ipm | | | | | |
| | Speed*2 Photo (4x6*) PP-201/Borderless | | approx. 60 sec. | | | | | | |
| | Borderless Printing*3 | | | Up to A4 | | | | | |
| | Standard Paper Input (Front Cassette/Tray) Plain Paper (Sheets) | | | A4/A5/B5/Letter=100/Legal=10 (Rear Tray) | | | | | |
| SCAN ** | Scanner Type/Scanning Method | | | Flatbed & ADF/ CIS (Contact Image Sensor) | Flatbed/CIS (Contact Image Sensor) | | NA | | |
| | Optical Resolution*5 | | | | 600 x 1200 dpi | | | NA | |
| | Scanning Speed*6 Reflective A4 Colour/300dp | | A4 Colour/300dpi | approx.19 sec. | | | NA | | |
| сорү | Maximum Document Size | | | A4/Letter (216x297 | | | , | | |
| | Copy Speed* ⁷ | Document: Colour | sFCOT/Simplex | | PE CONTRACTOR OFF | | approx. 32 sec. | NA | |
| | | | sESAT/Simplex | approx.3 | 3.5 ipm | approx. 2.5 ipm | approx.1.7 ipm | NA | |
| | | Document (ADF): Colour | sESAT/Simplex | approx. 2.5 ipm | | | NA | | |
| | Multiple Co | ру | Black/Colour | Max. 99 pages | Max. 20 pages | Max. 21 pages | Max. 20 pages | NA | |
| FAX | Transmission Speed*8 Black/Colour | | approx. 3 sec./ 1 min. (33.6 kbps) | NA | | | | | |
| | Transmission/Reception Memory*9 | | | approx. 50 pages | NA | | | | |
| | PC Fax | | | Windows/Mac. Available | NA | | | | |
| | Automatic Group Dialing | | | 19 locations | NA | | | | |
| NETWORK / SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS | Windows P | | lease visit | Windows 10 | 8.1/7 SP1 Windows 10/8/ 7/Vista/XP Windows 10/8.1/7 SP1 | | s 10/8.1/7 SP1 | | |
| | Macintosh | https://asia.canon/support to check OS compatibility and to download the latest driver updates. | | Mac OS X v10.10.5 ~v10.11, Mac OS v10.12 | NA | Mac OS X v10.7.5 and later | NA | | |
| | Operation I | Panel | Display | 2-Line LCD | 1.2" Segment LCD | NA | 1.2" Segment LCD | NA | |
| | | | Paper Handling (A4 Plain Paper) | 20-sheet | NA | | | | |
| | Interface | | Wireless LAN IEEE 802.11 b/g/n, USB 2.0 | | b/g/n, | USB 2.0 | | | |
| | Mobile Printing Applications | | | Canon PRINT, Easy-PhotoPrint+ | | NA | | | |
| | Other Connectivity Features | | | Mopria [®] Certified Canon Print Service, AirPrint, Cloud Service, Wireless Direct | Mopria [®] Certified Canon Print Service, Cloud Service, Access Point Mode | Canon Print Service, Cloud Service, Access Point Mode | NA | | |
| | Recommended Monthly Print Volume | | | 150-1,500 pages | | | | | |
| | Power Consumption (approx.) | | | 10W (0.9W Standby) | 11W (1.2W Standby) | 14W (1.7W Standby) | 9W (0.6W Standby) | 11W (0.6W Standby) | |
| | Dimensions (W x D x H) (approx.) | | | 445x330x197 mm | | 445x330x163 mm | | 445x330x135 mm | |
| | Weight (approx.) | | | 7.3 kg | 6.3 kg | 5.8 kg | 6.3 kg | 4.8 kg | |
| PAGE YIELD" | Plain Paper | r A4 | | A4 Colour Documents''': GI-790BK:6.000 GI-790C,M,Y: 7,000 | | | | | |
| PAGE Y | Photo Paper (PP-201) | | 4 x 6° Photos ^{**.} GI-790BK: NVA GI-790C ,M,Y: 2,000 | | | | | | |

Specifications are subject to change without notice.

- Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
 Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/IIS-CEI N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host
- computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc. ⁹ Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers.
- * Paper types NO1 supported to bordeness printing are as blows. Envelope, high resolution raper, r-shift fransler, Frond stuckers.
 * TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager that comes with the operating system.
- *5 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard
- ⁶ Colour document scan speed is measured with ISO/IEC 29183 Target A. Scan speed indicates the time measured between pressing the scan button of the scanner driver and the time the on-screen status display turns off. Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.
- ADF Copy speed is the average of ESAT in General Performance Test for the default simplex mode, ISO/IEC 24735, excluding time to copy the first set. Copy speed, page coverage, type of paper used etc. does not take into account warm-up time.
- Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Colour document fax transmission speed is based on default setting using Caron Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- *9 Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.
- *** Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.
- ¹¹ Declared yield value is the estimated value based on Canon individual test method using ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup.
 ¹² Declared vield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing

² Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial eutp. Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purposes.

Note: All printers work in Operating Environment of Temperature: 5-35°C; Humidity: 10-90% RH (no dew condensation

Canon

Delighting You Always

South & Southeast Asia Regional Headquarters: Canon Singapore Pte Ltd 1 Fusionopolis Place #14-10,Galaxis, Singapore 138522 Tel: 65-6799 8880 - Fax: 65-6799 8862

Tel: 65-6799 8888 • Fax: 65-679 https://asia.canon

Canon Singapore Pte Ltd. All rights reserved. This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by region. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.

https://www.facebook.com/CanonPrintingAsia



THE TEAM PLAYER THAT ALWAYS DELIVERS PIXMA INK EFFICIENT G SERIES

PIXMA Quality. Promised.



From Home to Office

Your most reliable partner at home or at work.

Canon



- ID card copying
- Mobile & cloud printing

#7000

[#]6000



Ideal for small offices







Canon

ріхма G1010

Refillable Ink Tank

Borderless photo printing

• Compact design

for High Volume Printing

in the second se

Best for student use

Perfect for small businesses