

Streamline Workflows with Collaborative Network Scanning

Designed for seamless connectivity, the **imageFORMULA DR-S350NW** A4 desktop scanner supports driverless and PC-less operation, enabling easy sharing of digitised documents with team members.

UP TO
50 PPM | 100 IPM*
FAST SCAN SPEED
*300 dpi, Greyscale, A4

UP TO
1,200 DPI
SCAN OUTPUT
RESOLUTION



SCAN UP TO A2*
*With Folio + Long Document mode



WI-FI &
ETHERNET



SCAN VIA
WEB BROWSER



4.3" INTUITIVE COLOUR LCD TOUCH PANEL

The LCD previews scanned images, enables creation of scan jobs (shortcuts), and displays help screens with GIFs and texts for streamlined scanner administration/ management.



SCAN & SHARE: WIDER RANGE OF DESTINATION OPTIONS

Easily send documents to predefined destinations, such as shared folder/ email*/ FTP/ FTPS/ printer/ SFTP.

*The DR-S350NW scan-to-email function now supports direct scanning to Teams and Slack.



BROWSER-BASED SCANNING

CaptureOnTouch Lite Web supports scanning directly through a web browser on your PC or smart devices, with no need for driver or software installation.

SPECIFICATIONS / imageFORMULA DR-S350NW

SCANNING		
Type		A4 Desktop Sheet-Fed Scanner (ADF)
Scanning Speed ^{*1}	Greyscale (Simplex/ Duplex)	200 dpi: 50 ppm/ 100 ipm 300 dpi: 50 ppm/ 100 ipm 600 dpi: 20 ppm/ 40 ipm
	Colour (Simplex/ Duplex)	200 dpi: 50 ppm/ 100 ipm 300 dpi: 40 ppm/ 80 ipm 600 dpi: 10 ppm/ 20 ipm
Scanning Element (Sensor)		Contact Image Sensor (CIS)
Light Source		Light-Emitting Diode (LED)
Scanning Side Capability		Simplex/ Duplex
Scanning Modes		Black and White, Greyscale, Colour, Active Threshold, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II
Other Features/ Functions		Skip Blank Page, Folio, Double Feed Detection, Double Feed Detection Ignore, Barcodes/ 2D Codes Detection
Optical Resolution		Up to 600 dpi
Output Resolution		100, 150, 200, 240, 300, 400, 600, 1200 dpi
Suggested Daily Volume (SDV)		6000-9000 sheets/ day
MEDIA		
Media Size (W x L)	Plain Paper	Min.: 50.8 x 54 mm Max.: 216 x 356 mm (Up to 5588 mm in Long Document Mode)
	Business Card	Min.: 50 x 85 mm Max.: 55 x 91 mm
	Plastic Card (ISO Standard)	86 x 54 mm
	Passport (ISO Standard)	125 x 88 mm
Media Thickness & Weight	Plain Paper	Separation Feed: 27-209 g/m ² (0.04-0.25 mm) Non-separation Feed: 27-255 g/m ² (0.04-0.3 mm)
	Business Card	128-255 g/m ² (0.15-0.3 mm)
	Plastic Card	1.4 mm or less
	Passport	4 mm or less (Passport + Carrier Sheet)
Output File Formats		PDF, JPEG, TIFF, PNG, PPTX, BMP, DOCX ^{*2} , XLSX ^{*2}
Automatic Document Feeder (ADF) Capacity ^{*3}		60 sheets
CONNECTIVITY & SOFTWARE		
Interface	USB	USB 3.2/ USB 2.0
	Ethernet	10Base-T/100Base-TX/1000Base-T
	Wi-Fi	IEEE802.11a/b/g/n/ac
Software		ISIS/ TWAIN/ WIA Driver, CaptureOnTouch
GENERAL		
Power Supply		AC 100-240V 50/60 Hz (Using AC adapter)
Power Consumption	Scanning (Max.)	23W
	Sleep Mode	1.8W
	Power Off (Max.)	0.1W
Operating Environmental Conditions	Temperature	10 to 35°C
	Humidity	20 to 80% RH
Dimensions (W x D x H)	Trays Closed	291 x 267 x 242 mm
	Trays Open	291 x 600 x 378 mm
Weight (Approx.)		3.4 kg (Without AC adapter)
REPLACEMENT COMPONENTS & ADD-ONS		
Consumables/ Options		Exchange Roller Kit, Carrier Sheet (Passport), Carrier Sheet (A4)
Accessories		Flatbed Scanner Unit 102, Flatbed Scanner Unit 202

^{*1} Conditions: Intel® Core™ i7 3.0 GHz CPU, 16GB memory, A4 portrait document size and orientation.

^{*2} DOCX and XLSX output are available only in CaptureOnTouch V5 Pro.

^{*3} Documents in A4 size or smaller, 80 g/m²; make sure stacks do not exceed 6 mm in height.



SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.
438A Alexandra Road, #06-10, Alexandra Technopark, Singapore 119967
Tel : 65-6799-8888 | Fax : 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.