

Conduit Adapter CA640-VB

- This accessory is used to connect camera to $\frac{3}{4}$ " inch NPS conduit pipe
- Dimension: (H x W x D)
33 x 94 x 134 mm
(1.30 x 3.70 x 5.28 in.)
- Weight: 230g (8.2oz.)
- Compatible with Canon VB-M640VE, VB-M641VE and VB-H651VE



Sunshade Cover SC640-VB

- This accessory is a cover used to protect camera from prolonged exposure to direct sunlight when wall mounted
 - Dimension: (H x W x D)
98 x 196 x 129 mm
(3.86 x 7.72 x 5.08 in.)
 - Weight: Approx. 140g (5.0oz.)
 - Compatible with Canon VB-H652LVE, VB-H651VE VB-M640VE and VB-M641VE



Heater Unit HU641-VB



- This accessory is a heater unit to allow camera usage in cold weather environments
 - Dimension: (H x W x D)
130 x 87 x 49 mm
(5.12 x 3.43 x 1.93 in.)
 - Weight: Approx. 60g (2.2oz.)
 - Compatible with Canon VB-H651VE and VB-M641VE

Pendant Mounting Kit PC640-VB

- This accessory is used for connecting camera to 1.5" NPS Pipe

- Dimension: (ϕ x H)
 ϕ 197 x 105 mm
(ϕ 7.76 x 4.13 in.)

- Weight: Approx. 750g (1.66lb.)

- Compatible with Canon VB-H761LVE-H, VB-H751LE-H, VB-M741LE-H, VB-H652LVE, VB-H761LVE, VB-H760VE, VB-R13, VB-H651VE, VB-H651V, VB-H751LE, VB-R11, VB-M641VE, VB-M641V, VB-M640VE, VB-M640V, VB-M741LE, VB-M740E



Tinted Capsule DU640-S-VB

- This accessory is a replacement smoked capsule
 - Dimension: (φ x H)
 φ 115 x 65 mm
(φ 4.53 x 2.56 in.) Weight:
Approx. 90g (3.2oz.)
 - Compatible with Canon VB-H651V, VB-H651VE, VB-M640V, VB-M641V, VB-M640VE, VB-M641VE



Hydrophilic Dome DU640-H-VB

- This accessory is a hydrophilic coated dome to replace existing dome to improve visibility in outdoor installation.

- Dimension: (φ x H)
 φ 115 x 65 mm

- (φ 4.53 x 2.56 in.) Weight:
Approx. 90g (3.2oz.)

- Compatible with Canon VB-H651VE, VB-M641VE and VB-M640VE



AC Adapter PA-V18 (Optional)

▪Dimension: (H x W x D) 32 x 60 x 130 mm
(1.26 x 2.36 x 5.12 in.), excluding projections.
Weight: Approx. 245 g (8.7 oz.) (excluding
power cable)

▪Input: 100 – 240 V AC, 50/60 Hz

▪Output: 13.1 V DC Max. 1.8 A (temperature: -
10°C – +35°C (+14°F – +95°F)), 13.1 V DC Max.
1.1 A (temperature: -10°C – +50°C (+14°F –
+122°F))

▪Operating Temperature: -10°C – +50°C (+14°F
– +122°F)
Humidity: 5% – 85% (without condensation)

▪Compatible with Canon VB-H761LVE-H,
VB-H751LE-H, VB-M741LE-H, VB-M50B, VB-
H652LVE, VB-H761LVE, VB-R13VE, VB-
R12VE, VB-R13, VB-H651VE, VB-H651V,VB-
H751LE, VB-R11VE, VB-R10VE, VB-R11, VB-
M641VE, VB-M641V, VB-M741LE, VB-
H45/B, VB-M44/B, VB-H43/B, VB-M42/B,
VB-H630VE, VB-H630D, VBH730F MK II, VB-
H730F, VB-M620VE, VB-M620D, VB-M720F.

